

said instructions configure said processing means to perform the steps of:

defining one of said text formatting templates as a two-dimensional template equipped with cartesian co-ordinates within a three-dimensional space;

equipping said defined text formatting template with three-dimensional preferences with which to format text to be included in said template;

equipping said defined text formatting template with said text; and

rendering said two-dimensional template including said text formatted according to said three-dimensional preferences within said three-dimensional space.

2. Apparatus according to claim 1, wherein said one or a plurality of text formatting templates is a two-dimensional plane delimited by two sets of two parallel segments of an identical length, the respective extremities of the segments of the first set intersecting the respective extremities of the segments of the second set at a right angle.

3. (AMENDED) Apparatus according to claims 1 or 2, wherein said defining step of one of said text formatting templates as a two-dimensional template equipped with cartesian co-ordinates within a three-dimensional space comprises either a two-dimensional rotation, or a three-dimensional rotation, or a scaling operation or any combination thereof.

4. Apparatus according to claim 3, wherein said two-dimensional rotation, three-dimensional rotation and scaling operation are implemented either by motion input or alphanumerical input or any combination thereof.

5. Apparatus according to claim 1, wherein said three-dimensional preferences with which to format text to be included in said template comprises either an extrusion depth, or one or a plurality of textures with which to equip said text, or one or a plurality of light sources with which to light said text, or any combination thereof.

6. Apparatus according to claim 5, wherein said extrusion depth, one or a plurality of textures with which to equip said text and one or a plurality of light sources with which to light said text are implemented either by motion input or alphanumeric input or any combination thereof.

7. Apparatus according to claim 1, wherein said text is one or a plurality of ASCII characters equipped with a font and font size, every outline of which is subsequently divided into a number of vertices, such that said every outline is divided into a number of segments that are tessellated into a number of polygons, with said number of polygons depending upon the final rendering resolution.

8. Apparatus according to claim 1, wherein said text equipping said defined text formatting template is alphanumeric data inputted either by means of physical input means or by means of a data source linked to said text formatting template.

9. Apparatus according to claim 1, wherein said equipping step of said defined text formatting template with said text is performed in real time.

10. Apparatus according to claim 1, wherein said rendering step of said two-dimensional template including said text formatted according to said three-dimensional preferences within said three-dimensional space is performed in real time.

11. A method of generating three-dimensional text within images composited in real time, comprising means for generating said three-dimensional text from one or a plurality of text formatting templates, including processing means and storage means, wherein

said storage means stores said text formatting templates and instructions for said processing means;

said instructions configure said processing means to perform the steps of:

defining one of said text formatting templates as a two-dimensional template equipped with cartesian co-ordinates within a three-dimensional space;

equipping said defined text formatting template with three-dimensional preferences with which to format text to be included in said template;

equipping said defined text formatting template with said text; and

rendering said two-dimensional template including said text formatted according to said three-dimensional preferences within said three-dimensional space.

12. A method according to claim 11, wherein said one or a plurality of text formatting templates is a two-dimensional plane delimited by two sets of two parallel segments of an identical length, the respective extremities of the segments of the first set intersecting the respective extremities of the segments of the second set at a right angle.

13. (AMENDED) A method according to claims 11 or 12, wherein said defining step of one of said text formatting templates as a two-dimensional template equipped with cartesian co-ordinates within a three-dimensional space comprises either a two-dimensional rotation, or a three-dimensional rotation, or a scaling operation or any combination thereof.

14. A method according to claim 13, wherein said two-dimensional rotation, three-dimensional rotation and scaling operation are implemented either by motion input or alphanumerical input or any combination thereof.

15. A method according to claim 11, wherein said three-dimensional preferences with which to format text to be included in said template comprises either an extrusion depth, or one or a plurality of textures with which to equip said text, or one or a plurality of light sources with which to light said text, or any combination thereof.



rendering said two-dimensional template including said text formatted according to said three-dimensional preferences within said three-dimensional space.

22. A computer-readable memory system having computer-readable data stored therein, comprising

one or a plurality of textures;

one or a plurality of object meshes;

an objects database;

one or a plurality of 3D text templates; and

a 3D text application with which to define, configure and render said 3D text templates.

23. A computer-readable memory system according to claim 22, wherein said program instructions are configured to;

define a text formatting templates as a two-dimensional template equipped with cartesian coordinates within a three-dimensional space;

equip said defined text formatting template with three-dimensional preferences with which to format text to be included in said template;

equip said defined text formatting template with said text; and

render said two-dimensional template including said text formatted according to said three-dimensional preferences within said three-dimensional space.